

**Submittal:** DWPCB1056B**STRONG-POINT<sup>®</sup> PHILLIPS BUGLE HEAD, COARSE THREAD, PHOSPHATE COATING**

Size	Part#	Case Qty.	Description
10 x 3-1/2	1031C	1M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
10 x 3-3/4	1033C	.8M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
10 x 4	1040C	.8M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
10 x 4-1/2	1041C	.5M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
10 x 5	1050C	.5M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
10 x 6	1060C	.5M	Phillips Bugle Head, Coarse Thread, Phosphate Coating

**Application:** Attaches gypsum board, foam, insulation to wood.

- Specifications:**
- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
  - Meets ASTM C 1002 for attaching gypsum board to steel studs

**Installation:** A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.<sup>1</sup>(American Society of Testing Materials)