



Submittal: DWPSB1056B





${\tt STRONG-POINT}^{\tt ®} \ {\tt PHILLIPS} \ {\tt BUGLE} \ {\tt HEAD}, \ {\tt FINE} \ {\tt THREAD}, \ {\tt PHOSPHATE} \ {\tt COATING}$

Size	Part#	Case Qty.	Description
10 x 3-1/2	1031	1M	Phillips Bugle Head, Fine Thread, Phosphate Coating
10 x 3-3/4	1033	.8M	Phillips Bugle Head, Fine Thread, Phosphate Coating
10 x 4	1040	.8M	Phillips Bugle Head, Fine Thread, Phosphate Coating
10 x 4-1/2	1041	.5M	Phillips Bugle Head, Fine Thread, Phosphate Coating
10 x 5	1050	.5M	Phillips Bugle Head, Fine Thread, Phosphate Coating
10 x 6	1060	.5M	Phillips Bugle Head, Fine Thread, Phosphate Coating
Application:	Attaches gypsum board to light gauge steel.		
Specifications:	 Meets ASTM¹ A 510 for carbon steel manufacturing Meets ASTM C 1002 for attaching gypsum board to steel studs 		
Features:	Type 'S' point for fastening gypsum to light gauge steel		

Installation:

A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.

¹(American Society of Testing Materials)