


**Submittal:** DWPCB0612B**STRONG-POINT<sup>®</sup> PHILLIPS BUGLE HEAD, COARSE THREAD, PHOSPHATE COATING**

Size	Part#	Case Qty.	Description
6 x 3/4	606C	15M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 1	610C	10M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 1-1/8	611C	10M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 1-1/4	614C	8M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 1-1/2	612C	6M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 1-5/8	615C	5M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 1-3/4	616C	4M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 2	620C	3.5M	Phillips Bugle Head, Coarse Thread, Phosphate Coating
6 x 2-1/4	624C	3M	Phillips Bugle Head, Coarse Thread, Phosphate Coating

**Application:** Attaches gypsum board to wood studs or used in light duty wood to wood applications. Also used in particle board attachments.

- Specifications:**
- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
  - Meets ASTM C 1002 for attaching gypsum board to steel studs

**Installation:** A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.

<sup>1</sup>(American Society of Testing Materials)