


**Submittal:** DWSCY0840Y**STRONG-POINT<sup>®</sup> SQUARE DRIVE BUGLE HEAD, COARSE THREAD, ZINC YELLOW**

Size	Part#	Case Qty.	Description
8 x 2-1/2	822QCY	2.5M	Square Drive Bugle Head, Coarse Thread, Zinc Yellow
8 x 3	830QCY	2M	Square Drive Bugle Head, Coarse Thread, Zinc Yellow

**Application:** Multi-purpose screw for interior or outdoor applications.  
Attaches gypsum board or wood to wood.

**Specifications:**

- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
- Product meets ASTM B-117 for salt spray corrosion testing

**Features:**

- 90/hr. salt spray resistance
- Square drive prevents cam out and stripping
- Used in low corrosion applications

**Coating:** The Zinc Yellow coating prevents the oxidation of steel by forming a protective barrier.

**Installation:** A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a #2 reduced Square drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.

<sup>1</sup>(American Society of Testing Materials)