

STRONG-POINT[®] Get the Point. Strong-Point.

Submittal: DSSTLT7WG0820



Size	Part#	Case Qty.	Description
8 x 1-1/4	XT814Y	8M	Star Drive Flat Head w/Nibs, Type '17', Zinc Yellow
8 x 1-5/8	XT815Y	5M	Star Drive Flat Head w/Nibs, Type '17', Zinc Yellow
8 x 2	XT820Y	3.5M	Star Drive Flat Head w/Nibs, Type '17', Zinc Yellow
Application:	For interior or outdoor applications.		
	Attaches wood to wood.		
Specifications:	• Meets ASTM ¹ A 510 for carbon steel manufacturing		
	 Product meets ASTM B-117 for salt spray corrosion testing 		
Features:	Yellow Zinc coating exceeds 180/hr. salt spray resistance		
	.0003 plating thickness		
	 Star Drive prevents cam out and stripping for improved driveability 		
	 Type '17' reduces wood splitting and eliminates the need for pre-drilling 		
	Nibs under head provide flush finish		
	Used in low corrosion applications		
Coating:	The Zinc Yellow coating prevents the oxidation of steel by forming a protective barrier.		
Installation:	A standard screw gun with torque limiting nose piece set at a maximum of 3000 RPM drive speed recommended. Use a T-20 Star		
	drive bit. Do not over torque as it can cause the head to snap or damage to the work surface.		



¹(American Society of Testing Materials)

XT814Y_XT820Y_Rev. A (7/9/15)