



Submittal: WWPBSPF0812L





$\mathsf{STRONG\text{-}POINT}^{\mathsf{®}}$ PHILLIPS FLAT HEAD PARTICAL BOARD SCREWS, PLAIN AND LUBED

Size	Part#	Case Qty.	Description
8 x 1-1/4	820L	8M	Phillips Flat Head Partical Board Screws, Plain and Lubed
8 x 1-1/2	824L	6M	Phillips Flat Head Partical Board Screws, Plain and Lubed
8 x 1-5/8	826L	5M	Phillips Flat Head Partical Board Screws, Plain and Lubed
8 x 1-3/4	828L	4M	Phillips Flat Head Partical Board Screws, Plain and Lubed
8 x 2	832L	3.5M	Phillips Flat Head Partical Board Screws, Plain and Lubed
Application:	Wood screws for interior wood applications. Cabinet work and furniture assembly.		
Specifications:	 Meets ASTM¹ A 510 for carbon steel manufacturing Product meets ASTM B-117 for salt spray corrosion testing 		
Features:	 Asymmetrical thread pattern Resists material slippage during pull out and vibration Superior holding power 		

Installation:

A standard screw gun with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Use a #2 reduced Phillips drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.

¹(American Society of Testing Materials)