

**Submittal:** CSHWH420BC



**STRONGCON® SLOTTED INDENTED HEX WASHER HEAD, HI-LOW, NOTCHED THREADS, DIAMOND POINT, CERAMIC COATING**

Size	Part#	Case Qty.	Description
1/4 x 1-1/4	CH420	3M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating
1/4 x 1-3/4	CH428	2M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating
1/4 x 2-1/4	CH436	1.5M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating
1/4 x 2-3/4	CH444	1M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating
1/4 x 3-1/4	CH452	1M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating
1/4 x 3-3/4	CH460	.5M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating
1/4 x 4	CH464	.5M	Slotted Indented Hex Washer Head, Hi-Low, Notched Threads, Diamond Point, Ceramic Coating

**Application:** Attaches wood or metal to concrete, brick, cement block or masonry.

- Specifications:**
- Meets ASTM<sup>1</sup> A 510 for carbon steel manufacturing
  - Product meets ASTM B-117 for salt spray corrosion testing

- Features:**
- Ceramic coating exceeds 500/hr. salt spray resistance
  - Designed to work with ACQ treated lumber
  - Notched threads for cutting into concrete, brick and cement block
  - Diamond Point design for cutting and clearing debris during installation

**Installation:** Pre-drill hole a minimum of 1/4" deeper than concrete screw to be embedded with a carbide masonry drill bit. Use a standard screw gun set at a maximum of 2500 RPM drive speed recommended. Use a 5/16" drill bit. Fastener is properly installed when head sits flush with the work surface. Do not over torque as it can cause the head to snap or stripping of the recess. Installed fasteners must be embedded into concrete, brick, cement block or masonry a minimum of 1".

<sup>1</sup>(American Society of Testing Materials)