

STRONG-POINT[®] Get the Point. Strong-Point.

Submittal: WWTCSQP620CB

${\tt STRONG-POINT}^{^{(\!0\!)}} {\tt FACE FRAMING \#7 SQUARE DRIVE PAN HEAD, COARSE THREAD, TYPE `17', {\tt BLACK OXIDE} }$

Size	Part#	Case Qty.	Description
6-20 x 1-1/4	XQ5C	8M	Face Framing #7 Square Drive Pan Head, Coarse Thread, Type '17', Black Oxide
6-20 x 1-1/2	XQ6C	7M	Face Framing #7 Square Drive Pan Head, Coarse Thread, Type '17', Black Oxide
Application:	Wood screws for cabinet framing assembly.		
Specifications:	 Meets ASTM¹ A 510 for carbon steel manufacturing Product meets ASTM B-117 for salt spray corrosion testing 		
Features:	 Type '17' reduces wood splitting and eliminates the need for pre-drilling Square drive prevents cam out and stripping Coarse thread for soft woods Superior holding power 		
Coating:	Black Oxide is a conversion coating that is used to add mild corrosion resistance and for appearance.		
Installation:	A standard screw gun with torque limiting nose piece set at a maximum of 2500 RPM drive speed recommended. Use a #2 reduced Square drive bit. The fastener is completely installed when the fastener head is seated flush with the work surface. Do not over torque as it can cause the head to snap or damage to the work surface.		

¹(American Society of Testing Materials)

XQ5C_XQ6C_Rev. A (2/24/16)